Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

- 1. (Original) An optical recording medium comprising a substrate, a light transmission layer and a plurality of recording layers between the substrate and the light transmission layer and capable of recording data in the plurality of recording layers and reproducing data recorded in the plurality of recording layers by projecting a laser beam via the light transmission layer onto the plurality of recording layers, at least one recording layer other than a farthest recording layer from the light transmission layer among the plurality of recording layers including a first recording film containing an element selected from a group consisting of Si, Ge, Sn, Mg, In, Zn, Bi and Al as a primary component and a second recording film located in the vicinity of the first recording film and containing an element selected from a group consisting of Cu, Al, Zn, Ti and Ag as a primary component.
- 2. (Original) An optical recording medium in accordance with Claim 1, wherein the first recording film contains Si as a primary component.
- 3. (Original) An optical recording medium in accordance with Claim 2, wherein the second recording film contains Cu as a primary component.
- 4. (Currently Amended) An optical recording medium in accordance with Claim 3, wherein at least one element selected from the group consisting of Al, Zn, Sn, Mg and Au and different from the element contained in the second recording layer as a primary component is added to the second recording film.

Application No. 10/613,525 Reply to Office Action dated March 7, 2006

- 5. (Original) An optical recording medium in accordance with Claim 4, wherein the second recording film is formed so as to be in contact with the first recording film.
- 6. (Original) An optical recording medium in accordance with Claim 3, wherein the light transmission layer has a thickness of 30 μ m to 200 μ m.
- 7. (Original) An optical recording medium in accordance with Claim 5, wherein the light transmission layer has a thickness of 30 μ m to 200 μ m.
- 8. (Original) An optical recording medium in accordance with Claim 3 which is further constituted so that data are recorded therein and data are reproduced therefrom by projecting a laser beam having a wavelength of 350 nm to 450 nm thereonto.
- 9. (Original) An optical recording medium in accordance with Claim 6 which is further constituted so that data are recorded therein and data are reproduced therefrom by projecting a laser beam having a wavelength of 350 nm to 450 nm thereonto.
- 10. (Original) An optical recording medium in accordance with Claim 7 which is further constituted so that data are recorded therein and data are reproduced therefrom by projecting a laser beam having a wavelength of 350 nm to 450 nm thereonto.
- 11. (Original) An optical recording medium in accordance with Claim 3 which is further constituted so that data are recorded therein and data are reproduced therefrom by employing an objective lens and a laser beam whose numerical aperture NA and wavelength λ satisfy λ /NA \leq 640 nm, and projecting the laser beam thereonto via the objective lens.
- 12. (Original) An optical recording medium in accordance with Claim 6 which is further constituted so that data are recorded therein and data are reproduced therefrom

3

Application No. 10/613,525

Reply to Office Action dated March 7, 2006

by employing an objective lens and a laser beam whose numerical aperture NA and wavelength λ satisfy $\lambda/NA \le 640$ nm, and projecting the laser beam thereonto via the objective lens.

13. (Original) An optical recording medium in accordance with Claim 7 which is further constituted so that data are recorded therein and data are reproduced therefrom

by employing an objective lens and a laser beam whose numerical aperture NA and wavelength λ

satisfy $\lambda NA \le 640$ nm, and projecting the laser beam thereonto via the objective lens.

14. (Currently Amended) An optical recording medium comprising a

substrate, a light transmission layer and a plurality of recording layers between the substrate and

the light transmission layer and capable of forming record marks in the plurality of recording

layers, thereby recording data therein and reproducing data recorded in the plurality of recording

layers by projecting a laser beam via the light transmission layer onto the plurality of recording

layers, at least one recording layer other than a farthest recording layer from the light

transmission layer among the plurality of recording layers being constituted so that a difference

in light transmittances between a region of a record mark formed by the irradiation of the laser

beam and blank regions is equal to or lower than 4 %.

15. (Original) An optical recording medium in accordance with Claim 14,

wherein the light transmission layer has a thickness of 30 μm to 200 μm.

16. (Original) An optical recording medium in accordance with Claim 14

which is further constituted so that data are recorded therein and data are reproduced therefrom

by projecting a laser beam having a wavelength of 350 nm to 450 nm thereonto.

17. (Original) An optical recording medium in accordance with Claim 15

which is further constituted so that data are recorded therein and data are reproduced therefrom

by projecting a laser beam having a wavelength of 350 nm to 450 nm thereonto.

4

Application No. 10/613,525

Reply to Office Action dated March 7, 2006

18. (Original) An optical recording medium in accordance with Claim 14

which is further constituted so that data are recorded therein and data are reproduced therefrom

by employing an objective lens and a laser beam whose numerical aperture NA and wavelength λ

satisfy $\lambda/NA \le 640$ nm, and projecting the laser beam thereonto via the objective lens.

19. (Original) An optical recording medium in accordance with Claim 15

which is further constituted so that data are recorded therein and data are reproduced therefrom

by employing an objective lens and a laser beam whose numerical aperture NA and wavelength λ

satisfy $\lambda NA \le 640$ nm, and projecting the laser beam thereonto via the objective lens.

20. (Original) A method for recording and reproducing data comprising the

steps of projecting a laser beam onto an optical recording medium comprising a substrate, a light

transmission layer and a plurality of recording layers between the substrate and the light

transmission layer and capable of recording data in the plurality of recording layers and

reproducing data recorded in the plurality of recording layers by projecting a laser beam via the

light transmission layer onto the plurality of recording layers, at least one recording layer other

than a farthest recording layer from the light transmission layer among the plurality of recording

layers including a first recording film containing an element selected from the group consisting

of Si, Ge, Sn, Mg, In, Zn, Bi and Al as a primary component and a second recording film located

in the vicinity of the first recording film and containing an element selected from a group

consisting of Cu, Al, Zn, Ti and Ag as a primary component, thereby causing the laser beam to

pass through the light transmission layer, and recording data in the plurality of recording layers

or reproducing data from the plurality of recording layers.

21. (Original) A method for recording and reproducing data in accordance

with Claim 20 wherein the first recording film of the optical recording medium contains Si as a

primary component.

5

Application No. 10/613,525 Reply to Office Action dated March 7, 2006

- 22. (Original) A method for recording and reproducing data in accordance with Claim 21 wherein the second recording film of the optical recording medium contains Cu as a primary component.
- 23. (Original) A method for recording and reproducing data in accordance with Claim 20 which comprises a step of irradiating the optical recording medium with a laser beam having a wavelength of 350 nm to 450 nm, thereby recording data in the optical recording medium or reproducing data from the optical recording medium.
- 24. (Original) A method for recording and reproducing data in accordance with Claim 22 which comprises a step of irradiating the optical recording medium with a laser beam having a wavelength of 350 nm to 450 nm, thereby recording data in the optical recording medium or reproducing data from the optical recording medium.
- 25. (Original) A method for recording and reproducing data in accordance with Claim 20 which comprises a step of employing an objective lens and a laser beam whose numerical aperture NA and wavelength λ satisfy λ /NA \leq 640 nm, and projecting the laser beam onto the optical recording medium via the objective lens, thereby recording data in the optical recording medium or reproducing data from the optical recording medium.
- 26. (Original) A method for recording and reproducing data in accordance with Claim 22 which comprises a step of employing an objective lens and a laser beam whose numerical aperture NA and wavelength λ satisfy λ /NA \leq 640 nm, and projecting the laser beam onto the optical recording medium via the objective lens, thereby recording data in the optical recording medium or reproducing data from the optical recording medium.
- 27. (New) An optical recording medium comprising a substrate, a light transmission layer and a plurality of recording layers between the substrate and the light transmission layer and capable of recording data in the plurality of recording layers and

Application No. 10/613,525 Reply to Office Action dated March 7, 2006

reproducing data recorded in the plurality of recording layers by projecting a laser beam via the light transmission layer onto the plurality of recording layers, at least one recording layer other than a farthest recording layer from the light transmission layer among the plurality of recording layers including a first recording film containing Si as a primary component and a second recording film located in the vicinity of the first recording film and containing Cu as a primary component.